



## Leading Features

- ▶ Three phase output
- ▶ Over 97.5% Max. efficiency
- ▶ 200V – 800V input voltage range
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Compact and light design for one-person easy installation
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 year standard, 8 year premium warranty, or extended options



Ginlong Technologies Co.,Ltd

Address: No. 57 Jintong Road, Binhai Industrial Park, Xiangshan,  
Ningbo, Zhejiang, 315712, China

Tel: +44 (0)113 328 0870 +86 (0)574 6578 1806 Fax: +86 (0)574 6578 1606

Email: info@ginlong.com Web: www.ginlong.com



solis australasia pty ltd

Address: 5/ 109 Tulip Street Cheltenham,  
Victoria, 3192 Australia

Tel: +61 (0)3 8555 9516  
Email: service@ginlongaust.com.au

Web: www.solisinverters.com.au

Model	Solis-6K
<b>Input Side</b>	
Max. DC input voltage	1000V
Start-up DC input voltage	330V
MPPT operating range	250-800V
Max. DC input current	15A+15A
Number of MPP/Max strings per MPPT	2/2
<b>Output Side</b>	
Rated output power	6kVA
Max. transient power	6.6kVA
Rated AC grid voltage	380V/400V/480V
AC grid voltage range	313~470V(adjustable), based on local requirement
Operating phase	three
Rated AC grid output current	9.1A/8.7A/7.2A
Max. AC output current	10.5A/10.0A/7.9A
Output power factor	0.8lagging/0.9lagging/1 adjustable
Grid current THD	Total THD<4%
DC injection current	<20mA
Rated grid frequency	50/60Hz
<b>Efficiency</b>	
Max. efficiency	>98%
Euro efficiency	>96.5%
MPPT efficiency	>99.9%
<b>Protection</b>	
DC reverse-polarity protection	Yes
AC short circuit protection	Yes
AC output overcurrent protection	Yes
Output overvoltage protection-Varistor	Yes
Ground fault monitoring	Yes
Grid monitoring	Yes
Islanding protection	Yes
Temperature protection	Yes
Integrated DC switch	Optional
<b>General Data</b>	
Size	430W*600H*220D(mm)
Weight	27kg
Topology	Transformerless
Internal consumption	<1W(Night)
Running temperature	-25°C~60°C
Ingress protection	IP65
Operating range utility frequency (Hz)	47-52 or 57-62(adjustable)
Noise emission(typical)	<30 dBA
Cooling concept	Natural convection
Max.operating altitude without derating	2000m
Designed lifetime	>20 years
Utility monitoring	Islanding protection $V_{ac}$ , $F_{ac}$ in accordance with UL 1741, G59/3, AS4777, VDE 0126-1-1
Operating surroundings humidity	0~95%
EMC	EN61000-6-1:2007 EN61000-6-3:2007
<b>Features</b>	
DC connection	MC-4 mateable
AC connection	IP67 rated plug
Display	LCD, 2 x 20 Z.
Interface	RS 485, WiFi/GPRS (optional)
Warranty	5~10 Years